

Bibliography

- [1] J. A. Stratton, *Electromagnetic Theory*, McGraw-Hill (1941).
- [2] J. D. Jackson, *Classical Electrodynamics*, John Wiley & Sons, 2nd ed. (1975).
- [3] L. D. Landau, E. M. Lifshitz, and L. P. Pitaevskii, *Electrodynamics of Continuous Media*, Pergamon Press, 2nd ed. (1984).
- [4] J. A. Stratton, *Electromagnetic Theory*, McGraw-Hill, pp. 16–23 (1941).
- [5] R. F. Harrington, *Time-harmonic Electromagnetic Fields*, McGraw-Hill, Inc. (1961).
- [6] M. Born and E. Wolf, *Principles of Optics*, Pergamon Press, sixth ed. (1980).
- [7] W. Smith, *Modern optical engineering*, McGraw-Hill, 2nd ed., pp. 301–346 (1990).
- [8] W. J. Smith, *Modern optical engineering*, McGraw-Hill, pp. 135–139 (1966).
- [9] A. Sommerfeld, *Partial differential equations in physics*, Academic Press, pp. 188–200 (1949).
- [10] G. C. Sherman, “Application of the convolution theorem to Rayleigh’s integral formulas,” *J. Opt. Soc. Am.*, vol. 57, pp. 546–547 (1967).
- [11] J. W. Goodman, *Introduction to Fourier Optics*, McGraw-Hill, pp. 42–46 (1968).
- [12] G. B. Airy, “On the diffraction of an object-glass with circular aperture,” *Transactions of the Cambridge Philosophical Society*, vol. 5, no. 3, pp. 283–291 (1835).
- [13] J. W. Goodman, *Introduction to Fourier Optics*, McGraw-Hill (1968).

- [14] D. G. Flagello and A. E. Rosenbluth, "Lithographic tolerances based on vector diffraction theory," *J. Vac. Sci. Technol. B*, vol. 10, no. 6, pp. 2997–3003 (1992).
- [15] G. M. Gallatin, "High numerical aperture scalar imaging," *Applied Optics*, vol. 40, no. 28, pp. 4958–4964 (2001).
- [16] D. C. O'Shea, *Elements of modern optical design*, John Wiley & Sons, pp. 111–114 (1985).
- [17] M. Born and E. Wolf, *Principles of Optics*, Pergamon Press, sixth ed., pp. 522–524 (1980).
- [18] H. Hopkins, "Canonical coordinates in geometrical and diffraction image theory," *Jpn. J. Appl. Phys.*, vol. 4, no. 1, pp. 31–35 (1965).
- [19] M. Born and E. Wolf, *Principles of Optics*, Pergamon Press, sixth ed., pp. 528–532 (1980).
- [20] Rayleigh, "Investigations in optics, with special reference to the spectroscope," *The Philosophical Magazine*, vol. 8, no. 49, pp. 261–274 (1879).
- [21] M. Born and E. Wolf, *Principles of Optics*, Pergamon Press, sixth ed., pp. 414–418 (1980).
- [22] D. Halliday and R. Resnick, *Physics*, John Wiley & Sons, extended ed., pp. 1034–1037 (1986).
- [23] A. K. Wong, *Resolution Enhancement Techniques in Optical Lithography*, SPIE Press (2001).
- [24] G. O. Reynolds, "A concept for a high resolution optical lithographic system for producing one-half micron linewidths," in H. L. Stover, ed., *Proc. SPIE*, vol. 633, pp. 228–238 (1986).
- [25] K. Kamon, T. Miyamoto, Y. Myoi, H. Nagata, M. Tanaka, and K. Horie, "Photolithography system using annular illumination," *Jpn. J. Appl. Phys.*, vol. 30, no. 11B, pp. 3021–3029 (1991).
- [26] M. Noguchi, M. Muraki, Y. Iwasaki, and A. Suzuki, "Subhalf micron lithography system with phase-shifting effect," in J. D. Cuthbert, ed., *Proc. SPIE*, vol. 1674, pp. 92–104 (1992).
- [27] H.-Y. Kang, C.-H. Kim, J.-H. Lee, W.-S. Han, and Y.-B. Koh, "High performance lithography with advanced modified illumination," *IEEE Transactions on Electronics*, vol. 77-C, no. 3, pp. 432–437 (1994).

- [28] T. Ogawa, M. Uematsu, T. Ishimaru, and M. Kimura, "The effective light source optimization with the modified beam for the depth-of-focus enhancements," in T. Brunner, ed., *Proc. SPIE*, vol. 2197, pp. 19–30 (1994).
- [29] B. J. Lin, "The attenuated phase-shifting mask," *Solid State Technology*, vol. 35, no. 1, pp. 43–47 (1992).
- [30] T. Terasawa, N. Hasegawa, and H. Fukuda, "Imaging characteristics of multi-phase-shifting and halftone phase-shifting masks," *Jpn. J. Appl. Phys.*, vol. 30, no. 11B, pp. 2991–2997 (1991).
- [31] M. Born and E. Wolf, *Principles of Optics*, Pergamon Press, sixth ed., pp. 265–268 (1980).
- [32] M. Levenson, N. Viswanathan, and R. Simpson, "Improving resolution in photolithography with a phase-shifting mask," *IEEE Transactions on Electron Devices*, vol. 29, no. 12, pp. 1812–1846 (1982).
- [33] L. Liebmann, I. Graur, W. Leipold, J. Oberschmidt, D. O'Grady, and D. Regaill, "Alternating phase shifted mask for logic gate levels, design and mask manufacturing," in L. van den Hove, ed., *Proc. SPIE*, vol. 3679, pp. 27–37 (1999).
- [34] H.-Y. Liu, L. Karklin, Y.-T. Wang, and Y. C. Pati, "The application of alternating phase-shifting masks to 140 nm gate patterning: Line width control improvements and design optimization," in *Proc. SPIE*, vol. 3236, pp. 328–337 (1998).
- [35] S. Nakao, A. Nakae, K. Tsujita, and W. Wakamiya, "Impact of spherical aberrations on printing characteristics of irregularly aligned patterns of alternating phase shift mask," *Jpn. J. Appl. Phys.*, vol. 38, no. 4A, pp. 1919–1926 (1999).
- [36] R. Schenker, "Effects of phase shift masks on across field linewidth control," in L. van den Hove, ed., *Proc. SPIE*, vol. 3679, pp. 18–26 (1999).
- [37] M. D. Levenson, "Extending the lifetime of optical lithography technologies with wavefront engineering," *Jpn. J. Appl. Phys.*, vol. 33, no. 12B, pp. 6765–6773 (1994).
- [38] B. J. Lin, "Partially coherent imaging in two-dimensions and theoretical limits of projection printing in microfabrication," *IEEE Transactions on Electron Devices*, vol. 27, no. 5, pp. 931–938 (1980).
- [39] F. M. Schellenberg, *Selected Papers on Resolution Enhancement Techniques in Optical Lithography*, SPIE Press (2004).

- [40] T. Toyoshima, T. Ishibashi, A. Minamide, K. Sugino, K. Katayama, T. Shoya, I. Arimoto, N. Yasuda, H. Adachi, and Y. Matsui, “0.1 μm level contact hole pattern formation with KrF lithography by resolution enhancement lithography assisted by chemical shrink (RELACS),” in *Technical Digest—International Electron Devices Meeting*, pp. 333–336 (1998).
- [41] A. Yariv, *Quantum electronics*, John Wiley & Sons, 3rd ed., pp. 663–665 (1989).
- [42] M. S. Yeung, D. Lee, R. Lee, and A. R. Neureuther, “Extension of the Hopkins theory of partially coherent imaging to include thin-film interference effects,” in J. Cuthbert, ed., *Proc. SPIE*, vol. 1927, pp. 452–463 (1993).
- [43] D. G. Flagello, *High Numerical Aperture Imaging in Homogeneous Thin Films*, Ph.D. thesis, University of Arizona (1993).
- [44] D. G. Flagello, T. Milster, and A. E. Rosenbluth, “Theory of high-NA imaging in homogeneous thin films,” *J. Opt. Soc. Am. A*, vol. 13, no. 1, pp. 53–64 (1996).
- [45] P. H. Berning, “Theory and calculations of optical thin films,” in G. Hass, ed., *Physics of Thin Films*, vol. 1, Academic Press, pp. 69–121 (1963).
- [46] T. A. Brunner, “Optimization of optical properties of resist processes,” in H. Ito, ed., *Proc. SPIE*, vol. 1466, pp. 297–308 (1991).
- [47] B. J. Lin, ed., *Journal of Microlithography, Microfabrication, and Microsystems*, vol. 3(1), SPIE Press, pp. 8–114 (2004).
- [48] V. N. Mahajan, *Aberration Theory Made Simple*, SPIE Press (1991).
- [49] F. Zernike, “Beugungstheorie des schneidenverfahrens und seiner verbesserten form, der phasenkontrastmethode,” *Physica*, vol. 1, pp. 689–704 (1934).
- [50] F. Zernike, “Diffraction theory of the knife-edge test and its improved form, the phase-contrast method,” *JM³*, vol. 1, no. 2, pp. 87–94 (2002).
- [51] M. Born and E. Wolf, *Principles of Optics*, Pergamon Press, sixth ed., pp. 203–207 (1980).
- [52] D. Malacara, *Optical shop testing*, John Wiley & Sons (1978).
- [53] D. G. Flagello, R. J. Socha, X. Shi, J. B. van Schoot, J. Baselmans, M. A. van de Kerkhof, W. de Boeij, A. Engelen, R. Carpaij, O. Noordman, M. H. Moers, M. Mulder, J. Finders, H. van Greevenbroek, M. Schriever, M. Maul, H. Haidner, M. Goepfert, U. Wegmann, and P. Graeupner, “Optimizing and

- enhancing optical systems to meet the low k_1 challenge,” in A. Yen, ed., *Proc. SPIE*, vol. 5040, pp. 139–150 (2003).
- [54] M. A. van de Kerckhof, W. de Boeij, H. Kok, M. Silova, J. Baselmans, and M. Hemerik, “Full optical column characterization of DUV lithographic projection tools,” in B. Smith, ed., *Proc. SPIE*, vol. 5377, pp. 1960–1970 (2004).
- [55] P. Dirksen, J. Braat, A. J. E. M. Janssen, and C. Juffermans, “Aberration retrieval using the extended Nijboer-Zernike approach,” *JM³*, vol. 2, no. 1, pp. 61–68 (2003).
- [56] D. Malacara, *Optical shop testing*, John Wiley & Sons, pp. 323–349 (1978).
- [57] N. R. Farrar, A. H. Smith, D. R. Busath, and D. Taitano, “In-situ measurement of lens aberrations,” in C. Proglor, ed., *Proc. SPIE*, vol. 4000, pp. 18–29 (2000).
- [58] G. Robins, K. Adam, and A. R. Neureuther, “Measuring optical image aberrations with pattern and probe based targets,” *J. Vac. Sci. Technol. B*, vol. 20, no. 1, pp. 338–343 (2002).
- [59] G. Robins and A. R. Neureuther, “Operational model for pattern and probe based aberration monitors,” *J. Vac. Sci. Technol. B*, vol. 20, no. 6, pp. 2510–2616 (2002).
- [60] M. Born and E. Wolf, *Principles of Optics*, Pergamon Press, sixth ed., pp. 424–428 (1980).
- [61] K. Toh, *Two-dimensional Images with Effects of Lens Aberrations in Optical Lithography*, Master’s thesis, University of California, Berkeley, memorandum No. UCB/ERL M88/30 (1988).
- [62] H. Gamo, “Matrix treatment of partial coherence,” in E. Wolf, ed., *Progress in Optics*, vol. 3, North-Holland, pp. 187–332 (1964).
- [63] Y. C. Pati, A. A. Ghazanfarian, and R. F. Pease, “Exploiting structure in fast aerial image computation for integrated circuit patterns,” *IEEE Transactions on Semiconductor Manufacturing*, vol. 10, no. 1, pp. 62–74 (1997).
- [64] A. E. Rosenbluth, G. Gallatin, R. Gordon, W. Hinsberg, J. Hoffnagle, F. Houle, K. Lai, A. Lvov, M. Sanchez, and N. Seong, “Fast calculation of images for high numerical aperture lithography,” in B. Smith, ed., *Proc. SPIE*, vol. 5377, pp. 615–628 (2004).
- [65] K. S. Yee, “Numerical solution of initial boundary value problems involving Maxwell’s equations in isotropic media,” *IEEE Transactions on Antennas Propagation*, vol. 14, pp. 302–307 (1966).

- [66] R. Guerrieri, K. H. Tadros, J. Gamelin, and A. Neureuther, "Massively parallel algorithms for scattering in optical lithography," *IEEE Transactions on Computer-aided Design of Integrated Circuits and Systems*, vol. 10, no. 9, pp. 1091–1100 (1991).
- [67] A. Wong and A. Neureuther, "Rigorous three-dimensional time-domain finite-difference electromagnetic simulation for photolithographic applications," *IEEE Transactions on Semiconductor Manufacturing*, vol. 8, no. 4, pp. 419–431 (1995).
- [68] M. S. Yeung, "Fast and rigorous three-dimensional mask diffraction simulation using Battle-Lemarie wavelet-based multiresolution time-domain method," in A. Yen, ed., *Proc. SPIE*, vol. 5040, pp. 69–77 (2003).
- [69] G. L. Wojcik, J. Mould, R. Ferguson, R. Martino, and K. K. Low, "Some image modeling issues for i-line 5x phase shifting masks," in T. Brunner, ed., *Proc. SPIE*, vol. 2197, pp. 455–465 (1994).
- [70] D. Nyyssonen and C. P. Kirk, "Optical microscope imaging of lines patterned in thick layers with variable edge geometry: theory," *J. Opt. Soc. Am. A*, vol. 5, no. 8, pp. 1270–1280 (1988).
- [71] K. Lucas, C.-M. Yuan, and A. Strojwas, "A rigorous and practical vector model for phase shifting masks in optical lithography," in J. D. Cuthbert, ed., *Proc. SPIE*, vol. 1674, pp. 252–263 (1992).
- [72] T. Matsuzawa, A. Moniwa, N. Hasegawa, and H. Sunami, "Two-dimensional simulation of photolithography on relective stepped substrate," *IEEE Transactions on Computer-aided Design of Integrated Circuits and Systems*, vol. 6, no. 3, pp. 446–451 (1987).
- [73] E. Barouch, B. Bradie, G. Karniadakis, and S. Orszag, "Comprehensive 3D simulator with non-planar substrates," in V. Pol, ed., *Proc. SPIE*, vol. 1264, pp. 334–342 (1990).
- [74] J. Bischoff, U. Glaubitz, and N. Haase, "New method of topography simulation in photolithography," in J. D. Cuthbert, ed., *Proc. SPIE*, vol. 1674, pp. 423–434 (1992).
- [75] M. Yeung and E. Barouch, "Three-dimensional nonplanar lithography simulation using a periodic fast multipole method," in G. Fuller, ed., *Proc. SPIE*, vol. 3051, pp. 509–521 (1997).
- [76] J.-P. Berenger, "A perfectly matched layer for the absorption of electromagnetic waves," *Journal of Computational Physics*, vol. 114, pp. 185–200 (1994).

- [77] J.-P. Berenger, "Three-dimensional perfectly matched layer for the absorption of electromagnetic waves," *Journal of Computational Physics*, vol. 127, pp. 363–379 (1996).
- [78] H. Kirchauer and S. Selberherr, "Rigorous three-dimensional photoresist exposure and development simulation over nonplanar topography," *IEEE Transactions on Computer-aided Design of Integrated Circuits and Systems*, vol. 16, no. 12, pp. 1431–1438 (1997).
- [79] A. Erdmann, C. Kalus, T. Schmoeller, Y. Klyonova, T. Sato, A. Endo, T. Shibata, and Y. Kobayashi, "Rigorous simulation of exposure over nonplanar wafers," in A. Yen, ed., *Proc. SPIE*, vol. 5040, pp. 101–111 (2003).
- [80] M. Zuniga, N. Rau, and A. Neureuther, "Application of a general reaction/diffusion resist model to emerging materials with extension to non actinic exposure," in *Proc. SPIE*, vol. 3049, pp. 256–268 (1997).
- [81] A. Erdmann, W. Henke, S. Robertson, E. Richter, B. Tollkühn, and W. Hoppe, "Comparison of simulation approaches for chemically amplified resists," in C. A. Mack and T. Stevenson, eds., *Proc. SPIE*, vol. 4404, pp. 99–110 (2001).
- [82] H. Fukuda, K. Hattori, and H. Takuya, "Impact of acid/quencher behavior on lithography performance," in C. Progler, ed., *Proc. SPIE*, vol. 4346, pp. 319–330 (2001).
- [83] W. Hinsberg, F. A. Houle, and H. Ito, "Reactive dissolution kinetics of lithographic copolymers," in J. L. Sturtevant, ed., *Proc. SPIE*, vol. 5376, pp. 352–359 (2004).
- [84] J. A. Sethian, "Fast marching level set methods for three-dimensional photolithography development," in G. Fuller, ed., *Proc. SPIE*, vol. 2726, pp. 262–272 (1996).
- [85] T. Brunner and R. Ferguson, "Simple models for resist processing effects," *Solid State Technology*, pp. 95–96,98,100,103 (1996).
- [86] C. A. Mack, "Enhanced lumped parameter model for photolithography," in *Proc. SPIE*, vol. 2197, pp. 501–510 (1994).
- [87] N. Cobb and A. Zakhor, "Fast sparse aerial-image calculation for OPC," in G. V. Shelden and J. N. Wiley, eds., *Proc. SPIE*, vol. 2621, pp. 534–545 (1995).
- [88] B. Tollkühn, A. Erdmann, J. Lammers, C. Nolscher, and A. Semmler, "Do we need complex resist models for predictive simulation of lithographic process performance?" in J. L. Sturtevant, ed., *Proc. SPIE*, vol. 5376, pp. 983–994 (2004).

- [89] M. D. Levenson, "The phase-shifting mask II: Imaging simulations and submicrometer resist exposures," *IEEE Transactions on Electron Devices*, vol. 31, no. 6, pp. 753–763 (1984).
- [90] A. Wong, R. Ferguson, S. Mansfield, A. Molless, D. Samuels, R. Schuster, and A. Thomas, "Level-specific lithography optimization for 1 Gb DRAM," *IEEE Transactions on Semiconductor Manufacturing*, vol. 13, no. 1, pp. 76–87 (2000).
- [91] A. Wong, R. Ferguson, and S. Mansfield, "The mask error factor in optical lithography," *IEEE Transactions on Semiconductor Manufacturing*, vol. 13, no. 2, pp. 235–242 (2000).
- [92] Y. Granik and N. B. Cobb, "MEEF as a matrix," in G. T. Dao and B. J. Grenon, eds., *Proc. SPIE*, vol. 4562, pp. 980–991 (2001).
- [93] A. Wong, R. Ferguson, L. Liebmann, S. Mansfield, A. Molless, and M. Neisser, "Lithographic effects of mask critical dimension error," in L. van den Hove, ed., *Proc. SPIE*, vol. 3334, pp. 106–116 (1998).
- [94] R. Kostelak, C. Pierrat, J. Garofalo, and S. Vaidya, "Exposure characteristics of alternate aperture phase-shifting masks fabricated using a subtractive process," *J. Vac. Sci. Technol. B*, vol. 10, no. 6, pp. 3055–3061 (1992).
- [95] C. Pierrat, A. Wong, and S. Vaidya, "Phase-shifting mask topography effects on lithographic image quality," in *Technical Digest—International Electron Devices Meeting*, pp. 53–56 (1992).
- [96] A. Wong and A. Neureuther, "Mask topography effects in projection printing of phase-shifting masks," *IEEE Transactions on Electron Devices*, vol. 41, no. 6, pp. 895–902 (1994).
- [97] A. K. Wong and A. R. Neureuther, "Polarization effects in mask transmission," in J. D. Cuthbert, ed., *Proc. SPIE*, vol. 1674, pp. 193–200 (1992).
- [98] A. K. Wong and C. Pierrat, "Wave-optical considerations in optical lithography," in F. Wyrowski, ed., *Proc. SPIE*, vol. 5182, pp. 63–72 (2003).
- [99] J. Kirk and C. Proglar, "Pupil illumination: In-situ measurement of partial coherence," in L. van den Hove, ed., *Proc. SPIE*, vol. 3334, pp. 281–288 (1998).
- [100] T. Brunner, "Impact of lens aberrations on optical lithography," *IBM J. Res. Develop.*, vol. 41, no. 1/2, pp. 57–67 (1997).
- [101] C. Proglar and D. Wheeler, "Optical lens specifications from the users' perspective," in L. van den Hove, ed., *Proc. SPIE*, vol. 3334, pp. 256–268 (1998).

- [102] D. G. Flagello, J. de Klerk, G. Davies, and R. Rogoff, "Towards a comprehensive control of full-field image quality in optical lithography," in G. Fuller, ed., *Proc. SPIE*, vol. 3051, pp. 672–685 (1997).
- [103] M. Born and E. Wolf, *Principles of Optics*, Pergamon Press, sixth ed., pp. 468–473 (1980).
- [104] B. J. Lin, "Where is the lost resolution?" in H. L. Stover, ed., *Proc. SPIE*, vol. 633, pp. 44–50 (1986).
- [105] J. Kirk, "Astigmatism and field curvature from pin-bars," in V. Pol, ed., *Proc. SPIE*, vol. 1463, pp. 282–291 (1991).
- [106] T. A. Brunner, A. L. Martin, R. M. Martion, C. P. Ausschnitt, and T. H. Newman, "Quantitative stepper metrology using the focus monitor test mask," in T. Brunner, ed., *Proc. SPIE*, vol. 2197, pp. 541–549 (1994).
- [107] A. Starikov, "Exposure monitor structure," in *Proc. SPIE*, vol. 1261, pp. 315–324 (1990).
- [108] C. P. Ausschnitt and M. E. Lagus, "Seeing the forest for the trees: a new approach to CD control," in *Proc. SPIE*, vol. 3332, pp. 212–220 (1998).
- [109] C. P. Ausschnitt, "Distinguishing dose from defocus for in-line lithography control," in B. Singh, ed., *Proc. SPIE*, vol. 3677, pp. 140–147 (1999).
- [110] J. C. Stover and M. L. Bernt, "Measurement and analysis of scatter from rough surfaces," in R. P. Breault, ed., *Proc. SPIE*, vol. 2260, pp. 40–49 (1994).
- [111] J. Kirk, "Scattered light in photolithographic lenses," in T. Brunner, ed., *Proc. SPIE*, vol. 2197, pp. 566–572 (1994).
- [112] C. Progler and A. Wong, "Zernike coefficients: are they really enough?" in C. Progler, ed., *Proc. SPIE*, vol. 4000, pp. 40–52 (2000).
- [113] A. K. Wong, A. F. Molless, T. A. Brunner, E. Coker, R. H. Fair, G. L. Mack, and S. M. Mansfield, "Linewidth variation characterization by spatial decomposition," *Journal of Microlithography, Microfabrication, and Microsystems*, vol. 1, no. 2, pp. 106–116 (2002).
- [114] A. K. Wong, A. F. Molless, T. A. Brunner, E. Coker, R. H. Fair, G. L. Mack, and S. M. Mansfield, "Characterization of line width variation," in C. Progler, ed., *Proc. SPIE*, vol. 4000, pp. 184–191 (2000).

- [115] P. Vanoppen, O. Noordman, J. Baselmans, and J. van Schoot, "Analysis of full wafer/full batch CD uniformity using electrical line width measurements," in C. Mack and T. Stevenson, eds., *Proc. SPIE*, vol. 4404, pp. 33–44 (2001).
- [116] "Techniques on microphotography," Kodak sales service publication P-52 (1963).
- [117] M. D. Prouty and A. R. Neureuther, "Optical imaging with phase shift masks," in *Proc. SPIE*, vol. 470, pp. 228–232 (1984).
- [118] J. Garofalo, C. Biddick, R. Kostelak, and S. Vaidya, "Mask assisted off axis illumination technique for random logic," *J. Vac. Sci. Technol. B*, vol. 11, no. 6, pp. 2651–2658 (1993).
- [119] J. Garofalo, O. Otto, R. Cirelli, R. Kostelak, and S. Vaidya, "Automated layout of mask assist-features for realizing $0.5k_1$ ASIC lithography," in T. Brunner, ed., *Proc. SPIE*, vol. 2440, pp. 302–312 (1995).
- [120] J. F. Chen, T. Laidig, K. Wampler, and R. Caldwell, "Optical proximity correction for intermediate-pitch features using sub-resolution scattering bars," *J. Vac. Sci. Technol. B*, vol. 15, no. 6, pp. 2426–2433 (1997).
- [121] O. Otto and R. Henderson, "Advances in process matching for rules-based optical proximity correction," in *Proc. SPIE*, vol. 2884, pp. 425–434 (1996).
- [122] N. Cobb and A. Zakhor, "Experimental results on optical proximity correction with variable threshold resist model," in G. Fuller, ed., *Proc. SPIE*, vol. 3051, pp. 458–468 (1997).
- [123] M. Rieger and J. Stirniman, "Mask fabrication rules for proximity corrected patterns," in *Proc. SPIE*, vol. 2884, pp. 323–332 (1996).
- [124] T. Waas, H. Eisenmann, and H. Hartmann, "Proximity correction for high CD-accuracy and process tolerance," in *Proc. Symposium on Nanocircuit Engineering* (1994).
- [125] H.-Y. Liu, L. Karklin, Y.-T. Wang, and Y. C. Pati, "Application of alternating phase-shifting masks to 140 nm gate patterning II: Mask design and manufacturing tolerances," in *Proc. SPIE*, vol. 3334, pp. 2–14 (1998).
- [126] A. N. Neureuther and C. G. Willson, "Reduction in x-ray lithography shot noise exposure limit by dissolution phenomena," *J. Vac. Sci. Technol. B*, vol. 6, no. 1, pp. 167–173 (1988).
- [127] G. M. Gallatin, "Continuum model of shot noise and line edge roughness," in C. A. Mack, ed., *Proc. SPIE*, vol. 4404, pp. 123–132 (2001).

- [128] R. L. Brainard, P. Trefonas, J. H. Lammers, C. A. Cutler, J. F. Mackevich, A. Trefonas, and S. A. Robertson, “Shot noise, LER, and quantum efficiency of EUV photoresists,” in R. S. Mackay, ed., *Proc. SPIE*, vol. 5374, pp. 74–85 (2004).
- [129] M. Born and E. Wolf, *Principles of Optics*, Pergamon Press, sixth ed., pp. 665–718 (1980).
- [130] A. E. Rosenbluth, G. Gallatin, N. Seong, O. Dittmann, and M. Totzeck, “Image formation in a lens with spatial dispersion,” in *Proc. 4th International Symposium on 157-nm Lithography* (2003).
- [131] N. Seong, K. Lai, A. E. Rosenbluth, and G. Gallatin, “Assessing the impact of intrinsic birefringence on 157-nm lithography,” in B. Smith, ed., *Proc. SPIE*, vol. 5377, pp. 99–103 (2004).
- [132] E. C. Kintner, “Method for the calculation of partially coherent imagery,” *Applied Optics*, vol. 17, no. 17, pp. 2747–2753 (1978).
- [133] S. Subramanian, “Rapid calculation of defocused partially coherent images,” *Applied Optics*, vol. 20, no. 10, pp. 1854–1857 (1981).
- [134] R. L. Gordon and A. E. Rosenbluth, “Lithographic image simulation for the 21th century with 19th-century tools,” in F. Wyrowski, ed., *Proc. SPIE*, vol. 5182, pp. 73–87 (2003).
- [135] E. D. Palik, ed., *Handbook of optical constants of solids*, Academic Press (1985).
- [136] A. J. Warnecke and P. J. Lopresti, “Refractive index dispersion in semiconductor-related thin films,” *IBM J. Res. Develop.*, pp. 256–262 (1973).

Index

- Abbe's method, *see* source points integration
- aberration
 - astigmatism, 141
 - balancing, 139
 - coma, 142
 - defocus, *see* defocus
 - displacement theorem, 135–136
 - piston, 141
 - Seidel theory, 133
 - shamrock, 142
 - spherical, 143
 - tilt, 141
- absorption coefficient, 14
- aerial image, 107
- Airy pattern, *see* diffraction, Fraunhofer, circular aperture
- alternating phase-shifting mask, *see* resolution enhancement, alternating phase-shifting mask
- angular frequency, *see* frequency, angular
- aquatic image, 107
- astigmatism, *see* aberration, astigmatism
- attenuated phase-shifting mask, *see* resolution enhancement, attenuated phase-shifting mask
- attenuation index, *see* extinction coefficient
- auto-coherence function, *see* coherence, spatial, auto-coherence function
- auto-correlation function, 73
- balancing, *see* aberration, balancing
- Bessel function, 47
- bias
 - mask
 - order equalization, 95
 - process, 94, 170
- binary intensity object, 78
- birefringence, *see* refraction, double form, 195 stress, 195
- Brewster angle, 115
- canonical coordinates, 67
- characteristic impedance, 8
- characteristic matrix, 120
 - transverse electric, 120
 - transverse magnetic, 121
- circle function, 207
- circular polarization, *see* polarization, circular
- coherence
 - spatial, 58–64
 - auto-coherence function, 59
 - coherent, 60
 - complex degree of coherence, *see* complex degree of coherence
 - incoherent, 60
 - mutual intensity, *see* mutual intensity
 - partially coherent, 60
 - temporal, 58
 - coherence length, 17
 - coherence time, 17, 197

- quasi-monochromatic light, 14–18
- coherence length, *see* coherence, temporal, coherence length
- coherence time, *see* coherence, temporal, coherence time
- coherency matrix, *see* polarization, coherency matrix
- coherent decomposition, 157–159
- coma, *see* aberration, coma
- complex correlation factor, *see* polarization, complex correlation factor
- complex degree of coherence, 60, 61
 - Köhler illumination, 66
 - quasi-monochromatic light, 60
- condenser lens, 65
- conductivity, 3
- constitutive relations, 3
- continuity equation, 2
- contrast, 87
- coupling image, 107
- defocus, 141, 179–181
 - Rayleigh's unit, 180
- degree of first-order modulation, 85
 - alternating phase-shifting mask, 88
 - attenuated phase-shifting mask, 86
 - off-axis illumination, 85
- degree of polarization, *see* polarization, degree of
- dielectric constant, *see* permittivity
- dielectric tensor, 191
- diffraction
 - Fraunhofer, 41–44
 - annular aperture, 46–49
 - circular aperture, 46–49, 93
 - rectangular aperture, 45–46
 - relationship with transfer function, 55
 - scaling, 49
 - Fresnel, 35–39
 - pattern, *see* point spread function
 - Rayleigh-Sommerfeld, 39–41
 - diffraction focus, 135
 - direction cosines, 103
 - dispersion, 17
 - displacement theorem, *see* aberration, displacement theorem
 - divergence theorem, 18
 - dose to clear, 167, 185
 - dose to harden, 167
 - dose to print, *see* exposure dose
 - dose variation, 182–183
 - double refraction, *see* refraction, double
 - edge roughness, *see* mask-edge roughness or line-edge roughness
 - effective source, 68
 - eikonal, 20
 - eikonal equation, 20
 - elliptic polarization, *see* polarization, elliptic
 - energy density, 4
 - geometrical optics, 20
 - ergodicity, 197
 - evanescent wave, 116
 - exposure dose, 167, 185
 - extinction coefficient, 13
 - feature, 165
 - flare, 183–186
 - flare-amplification factor, 186
 - fluctuation, 165
 - focal length, 26
 - focal plane, 26
 - focus, *see* defocus; diffraction focus
 - Fraunhofer diffraction, *see* diffraction, Fraunhofer
 - frequency, 10
 - angular, 10
 - Fresnel diffraction, *see* diffraction, Fresnel
 - Fresnel's formulae, 111–112

- fringe visibility, *see* contrast
- Fringe Zernike, *see* Zernike polynomial, Fringe Zernike convention
- Gauss's law, 18
- Green's function, 34
- Green's theorem, 49
- group velocity, *see* velocity, group
- half-pitch
 - minimum, 75, 89–90
 - alternating phase-shifting mask, 89
 - coherent illumination, 80
 - general, 77
 - off-axis illumination, 84
 - partially coherent illumination, 83
- harmonic wave, *see* wave, harmonic
- Hartmann test, 146–147
- Hopkins' approach, *see* transmission cross-coefficient
- Huygens-Fresnel principle, 37
- illumination
 - critical, 65
 - Köhler, 65–67
- immersion lithography, 126–127
- incoherent, *see* coherence, spatial, incoherent
- inherent variation, 165
- intensity
 - definition, 5
 - normalization, 55–56
- internal reflection, *see* total internal reflection
- k_1 , 94
 - lithography difficulty, 165
 - mask-error factor, 171
 - proximity effect, 170
- $k_{1\text{half-pitch}}$, 90
 - lithography difficulty, 165
- mask-error factor, 171
 - proximity effect, 170
- k_2 , 181
- Köhler illumination, *see* illumination, Köhler
- Kirchhoff's approximations, 36
- latent image, 126
- law of reflection, 109
- law of refraction, *see* Snell's law
- line spread function, 172
- line-edge roughness
 - photoresist, 189
- linear polarization, *see* polarization, linear
- Lorentz force equation, 3, 97
- magnification
 - angular, 28
 - immersion, 127
 - lateral, 26
 - immersion, 127
 - longitudinal, 28
 - immersion, 127
- mask-edge roughness, 175
- mask-error enhancement factor, *see* mask-error factor
- mask-error factor, 170–173
- material equations, *see* constitutive relations
- Maxwell's equations, 2
 - integral form, 2
- mean-square wavefront deformation, 137
- meridional plane, 103
- Michelson interferometer, 144
- minimum dimension, 75, 90–94
- minimum half-pitch, *see* half-pitch, minimum
- minimum pitch, *see* half-pitch, minimum
- mutual coherence function, 59
- quasi-monochromatic light, 60

- mutual intensity, 61
- Nijboer-Zernike method, 144–146
- numerical aperture, 54
- obliquity factor, 56–58
 - immersion, 127
- off-axis illumination, *see* resolution enhancement, off-axis illumination
- Ohm's law, 3
- optical and process correction, *see* resolution enhancement, optical and process correction
- optical path, *see* eikonal
- optical proximity correction, *see* resolution enhancement, optical and process correction
- p*-polarization, *see* polarization, transverse magnetic
- paraxial ray, 24
- partial coherence factor, 68
- partially coherent, *see* coherence, spatial, partially coherent
- periodic space, 78
- permeability, 3
- permittivity, 3
 - principal, 194
- phase error, 174–175
- phase velocity, *see* velocity, phase
- phase-contrast method, 149
- phase-edge mask, *see* resolution enhancement, phase-edge mask
- phase-shifting mask, *see* resolution enhancement
- phasor, 11, 12
- photoresist roughness, *see* line-edge roughness, photoresist
- physical optics, *see* diffraction
- piston, *see* aberration, piston
- pitch, *see* half-pitch
- plane of incidence, 108
- plane wave, *see* wave, plane
- point spread function, 44, *see also* diffraction
- polarization, 97–102
 - circular, 98
 - coherency matrix, 99
 - complex correlation factor, 99
 - degree of, 98, 101, 177
 - upon reflection and transmission, 114
 - elliptic, 98
 - linear, 98
 - parallel, *see* polarization, transverse magnetic
 - perpendicular, *see* polarization, transverse electric
 - transverse electric, 103, 117
 - image, 128
 - transverse magnetic, 103, 117
 - image, 128
- polarization-induced stray light, 107, 128
- polarizing angle, *see* Brewster angle
- Poynting vector, 4
 - geometrical optics, 20
 - harmonic wave, 12
 - plane wave, 8
- Poynting's theorem of energy conservation, 4
- principal dielectric constant, *see* permittivity, principal
- principal permittivity, *see* permittivity, principal
- principal propagation velocity, *see* velocity, principal propagation
- process bias, *see* bias, process
- projection lens, 26
- proximity effect, 167–170
- pupil, 44
- pupil function, 52, *see also* transfer function, coherent
 - aberration-free, 53

- quadrant function, 158
- quarter-wave plate, 243
- quasi-monochromatic light, *see* coherence, temporal, quasi-monochromatic light
- radiation condition, *see* Sommerfeld radiation condition
- ray aberration, 140
- Rayleigh's resolution, *see* resolution, Rayleigh's criterion
- Rayleigh's unit, *see* defocus, Rayleigh's unit
- Rayleigh-Sommerfeld diffraction, *see* diffraction, Rayleigh-Sommerfeld
- reciprocity, 33–34
 - scalar field, 34
 - vector field, 34
- reduction system, 28
- reflection, 108–109
- reflection coefficient, 111–112, 122–123
- reflectivity, 113
- refraction, 108–109
 - double, 195
- refractive index, 6
- relaxation time, 233
- resist image, 107
- resolution, *see* also half-pitch
 - Rayleigh's criterion, 75, 93
- resolution enhancement
 - alternating phase-shifting mask, 87, 89
 - attenuated phase-shifting mask, 85–87, 94
 - off-axis illumination, 83–84
 - optical and process correction, 188
 - phase-edge mask, 91
- s-polarization, *see* polarization, transverse electric
- Seidel theory of aberrations, *see* aberration, Seidel theory
- shamrock, *see* aberration, shamrock
- shot noise, 188
- sinc function, 45
- Snell's law, 23, 109
- Sommerfeld radiation condition, 36
- source points integration, 155–157
- speed, *see* velocity
- spherical aberration, *see* aberration, spherical
- spherical wave, *see* wave, spherical
- stationarity, 197
- Stoke's theorem, 18
- stratified medium, 116
- Strehl ratio, 135
- telecentricity error, 84, 177
- thin lens, 24–26
- thin-mask approximation, *see* thin-object approximation
- thin-object approximation, 159
- threshold intensity, 167, 188
 - relation to exposure dose, 167
- tilt, *see* aberration, tilt
- time-domain finite-difference, 160, 174
- total internal reflection, 115–116
- transfer function
 - coherent, 51, *see also* pupil function
 - incoherent, 73
 - relationship with Fraunhofer diffraction pattern, 55
 - with obliquity factor, 57
- transmission coefficient, 111–112, 122–123
- transmission cross-coefficient, 70
 - computation, 153–155
- transmission error, 174–175
- transmissivity, 113
- transverse electric, *see* polarization, transverse electric
- transverse magnetic, *see* polarization, transverse magnetic

- van Cittert-Zernike theorem, 63
 - Köhler illumination, 67
- velocity
 - electromagnetic wave, 6
 - group, 16, 234
 - phase, 234
 - principal propagation, 194
- vignetting, 65, 179

- wave
 - equation, 5
 - harmonic, 9–14
 - plane, 6–8
 - spherical, 9
- wave equation, *see* wave, equation
- wave number, 10
- wavelength, 10

- Zernike phase-contrast method, *see* phase-contrast method
- Zernike polynomial, 137–140
 - Fringe Zernike convention, 140